

Thin wall heat shrink tubing

- International industrial specifications • UL 224 125 ° C VW1 600V, RoHS.
- Flame retardant.
- 2/1 shrinkage from 70 ° C.
- Temperature for full shrinkage: + 100 ° C.
- Operating temperature: -55 ° C / + 135 ° C.
- Standard colors: Black, red, yellow, blue, white, green, transparent.
- Non-standard colors: Gray, purple, orange, brown, green / yellow.



Reference	Mini expanded/maxi recovered diameter	Wall thickness after constriction	1 meter bar packaging
TFE-3/64	1.2/0.6	0.40	10
TFE-1/16	1.6/0.8	0.43	10
TFE-3/32	2.4/1.2	0.51	10
TFE-1/8	3.2/1.6	0.51	10
TFE-3/16	4.8/2.4	0.51	10
TFE-1/4	6.4/3.2	0.64	10
TFE-3/8	9.5/4.8	0.64	10
TFE-1/2	12.7/6.4	0.64	10
TFE-3/4	19.0/9.5	0.76	5
TFE-1	25.4/12.7	0.89	5
TFE-1.1/4	32.0/16.0	1.02	5
TFE-1.1/2	38.0/19.0	1.02	5
TFE-2	50.8/25.4	1.14	5
TFE-3	76.5/38.1	1.27	5
TFE-4	101.6/50.8	1.40	5

* Add the color behind the reference.