

Tinned bare copper cable

- Annealed tinned bare copper cable.
- DIN 48201/1 and DIN VDE 0295 standards.
- Driver in class 2.
- Tinned bare copper.
- Radius of curvature: 6 x the diameter.
- Bend radius: 7.5 x Cable diameter.



| Référence | Section mm ² | Max diameter (mm) | Weight (Kg/Km) | Setting-up (qty & wire diameter in mm) | Conditionnement (m) |
|-----------|-------------------------|-------------------|----------------|--|---------------------|
| CNR-10E | 10 | 4.1 | 96 | 7x1,35 | Coil/Drum |
| CNR-16E | 16 | 5.1 | 154 | 7x1,7 | Coil/Drum |
| CNR-25E | 25 | 6.3 | 240 | 7x2,1 | Coil/Drum |
| CNR-35E | 35 | 7.5 | 336 | 7x2,5 | Coil/Drum |
| CNR-50E | 50 | 9.0 | 480 | 19x1,8 | Coil/Drum |
| CNR-70E | 70 | 10.5 | 672 | 19x2,1 | Coil/Drum |
| CNR-95E | 95 | 12.5 | 912 | 19x2,5 | Coil/Drum |
| CNR-120E | 120 | 14.1 | 1152 | 37x1,99 | Coil/Drum |
| CNR-150E | 150 | 15 | 1440 | 37x3,2 | Coil/Drum |
| CNR-240E | 240 | 19 | 2304 | 61x2,32 | Coil/Drum |

* Managed from stock from 35 to 120 mm², other sections on manufacture with mini launch